

## 7006 矩陣掃描器



7006 系列多通道掃描器可搭配 ESA 與 SE 系列組成多點測試功能，可彈性組成不同測試模組，亦可增加待測物 (DUT) 數量，解決複雜配線操作困難，提昇測試效率增加產能。

### 產品特色

- 最大可提供 80 個輸出通道供測試切換 (1 台 master 搭配 4 台 slave)。

### 7006 產品規格

型號	7006
<b>輸入電源</b>	
電壓	N/C
高電壓通道 (H.V)	5kVac/6kVdc
高電流通道 (H.A.)	40Aac
標準模組	1 module (8 H.V. channels)
最多可安裝模組	Maximum 2 models can be mounted
選購模組	1 module can be mounted in addition to the standard module Either 8 H.V. or 8 H.A. modules can be selected from Optional items
<b>一般規格</b>	
控制模組 (選購)	Include GPIB or USB & RS232 Interface and Power module ( Input Power 115V/230Vac ± 15%, 50Hz/60Hz ± 5%, max. current 2A )
多台連機	7006 + Master module acts as master to control slave units (Max 4 units) This makes this system total 80 channels. (16ch/unit x 5 units = 80 ch)
操作溫度 / 儲存溫度 / 濕度	0 to 40°C/-40 to 75°C/20 to 80%RH
尺寸 (寬 x 高 x 深), mm	430 x 89 x 300
重量	9.5kg Max.

#### 標準配件

1105 Hipot and Scanner Linking Lead\*1; 1109 Hipot Output Lead - Pin Connector\*8; 1111 External Scanner Communication Cable\*1

\*Product specifications are subject to change without notice

### 產品型號

- 7006 Matrix Scanner (8 H.V. scanner inclusive as standard)

### 選購功能

- OPT.743 8 H.V. channels module for AC-W/DC-W or IR testing
- OPT.744 8 H.A. channels module for Ground Bond testing
- OPT.791 Master module with GPIB Interface
- OPT.792 Master module with USB & RS232 Interface

Note: OPT.791 & OPT.792 are mutually exclusive, only one Option can be selected